

# SAFETY DATA SHEET

## PRESOAK POWDER

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME                    PRESOAK POWDER  
 PRODUCT NO.                     HAD057  
 INTERNAL ID                     422  
 SUPPLIER                         NIVEK CATERING SUPPLIES LTD.  
    UNITS 14 & 15  
    WOODFALLS INDUSTRIAL  
    ESTATE  
    LADDINGFORD, nr YALDING  
    MAIDSTONE  
    KENT ME18 6DA  
    TEL: 01622 871714  
    FAX: 01622 873379

### 2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
Isononylphenol Ethoxylate		68412-54-4	1-5%	Xn;R22. Xi;R41. R53.
SODIUM ALKYL BENZENE SULPHONATE		25155-30-0	1-5%	Xi;R38,R41.
SODIUM CARBONATE	207-838-8	497-19-8	30-60%	Xi;R36
TriSodium Phosphate (Hydrated)		10101-89-0	30-60%	Xi;R36/38.

The Full Text for all R-Phrases are Displayed in Section 16

### 3 HAZARDS IDENTIFICATION

Irritating to eyes and skin.

CLASSIFICATION                    Xi;R36/38.

### 4 FIRST-AID MEASURES

#### INHALATION

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

#### INGESTION

**DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS!**

Rinse mouth thoroughly. Promptly get affected person to drink large volumes of water to dilute the swallowed chemical. Get medical attention immediately! Provide rest, warmth and fresh air.

#### SKIN CONTACT

Important to remove the substance from the skin immediately. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing. Chemical burns must be treated by a physician.

#### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

# PRESOAK POWDER

## 6 ACCIDENTAL RELEASE MEASURES

### SPILL CLEAN UP METHODS

DO NOT TOUCH SPILLED MATERIAL! Wear necessary protective equipment. Collect and reclaim or dispose in sealed containers in licensed waste. Avoid generation and spreading of dust. Flush area with plenty of water.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Persons with impaired lung functions should not handle this preparation. Avoid handling which leads to dust formation. Provide good ventilation.

### STORAGE PRECAUTIONS

Store in tightly closed original container in a cool, dry well-ventilated place. Keep in original container.

### STORAGE CLASS

Chemical storage.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### INGREDIENT COMMENTS

OES = Occupational Exposure Standard.

### PROTECTIVE EQUIPMENT



### ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation. Provide sufficient ventilation for operations causing dust formation.

### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Occupational Exposure Limit. Wear respirator if there is dust formation.

### HAND PROTECTION

Use protective gloves.

### EYE PROTECTION

Use approved safety goggles or face shield.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Powder
COLOUR	Colourless to pale yellow
ODOUR	Odourless
BULK DENSITY	N/A.

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions.

### CONDITIONS TO AVOID

Avoid contact with: Strong mineral acids.

# PRESOAK POWDER

## 11 TOXICOLOGICAL INFORMATION

### INHALATION

May cause irritation to the respiratory system.

### INGESTION

May cause discomfort if swallowed.

### SKIN CONTACT

May cause skin irritation/eczema Powder may irritate skin.

### EYE CONTACT

Irritation of eyes and mucous membranes.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

Not regarded as dangerous for the environment.

## 13 DISPOSAL CONSIDERATIONS

### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

## 14 TRANSPORT INFORMATION

UN NO. ROAD

0

## 15 REGULATORY INFORMATION

### LABELLING



Irritant

### RISK PHRASES

R36/38 Irritating to eyes and skin.

### SAFETY PHRASES

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S37 Wear suitable gloves.  
S24/25 Avoid contact with skin and eyes.  
S60 This material and its container must be disposed of as hazardous waste.

### ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980.

### EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EEC.

### STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

### APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

### GUIDANCE NOTES

Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

## 16 OTHER INFORMATION

# PRESOAK POWDER

## GENERAL INFORMATION

This information is given in good faith and is based upon current available data. The suitability of this product for any particular use is not suggested. The user must determine if the product is correct for any particular application. This document is not a specification. Conforms to 2001/58/EC

REVISION DATE 10.01.2005

REV. NO./REPL. SDS GENERATED 04

SDS NO. 422NK

DATE 10.01.2005

## RISK PHRASES IN FULL

R22 Harmful if swallowed.

R36 Irritating to eyes.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R53 May cause long-term adverse effects in the aquatic environment.